



June 17, 2024

Technical Service Bulletin – 09

Mustang Dark Horse R Engine Calibration

Issue: A revised calibration has been released (2024DarkHorseR_V5) to address an engine speed limit that occurred for 120 seconds after each engine start up.

Action:

• Follow the procedure to update your PCM calibration

Procedure: Follow the flashing procedure from your Owner's Manual

Install ProCal Software on Computer

 Navigate your browser to https://performanceparts.ford.com/download/ and click on "ProCal 4 Installer Download (.zip)"



• Extract the files to your computer in a memorable location and run the "setup" file. Follow the prompts to install ProCal.

Updating ProCal Firmware

- Connect the ProCal tool with the USB cable provided and plug it into the computer.
- Open ProCal with the desktop icon (or from the start menu).

Attention: Some company networks may have security set to block access to downloads. Please contact your network's IT administrator if you have problems connecting.



• If database version updates are available, select "Yes."

ProCal		\times				
Database update is availble. Version 34 Would you like to update?						
	Yes	No				

If PID updates are available, select "Yes."



- When prompted Disconnect the USB cable and plug it back in to power cycle the ProCal. Press "O.K."
 - Note: The ProCal tool may take a minute to load.



• The ProCal Device Information should populate. The software version will have to be updated to at least a 2.204 version to flash the calibration to the Dark Horse PCM. If this is not a high enough version press the "Update" button to update the firmware. Follow the prompts to update.

 ProCal v2.967 	2	_		\times
Connect Log Files				
Device Information		_		
Version:	2.120		Update	
Serial Number:	0CB86D88			
Rags:	0000			
Credits Available:	1			
Credits Used:	0			
VINs:				
Vehicle Files:				
۲.				•
Connected				

Flashing Calibration into the Vehicle

Note: The Dark Horse R requires a "Force Flash" be done when updating the PCM calibration. This does require a special procedure and unlock code.

• Plug the ProCal into the OBDII port of the vehicle.



• After the PROCAL loads, press and hold "ABOUT DEVICE" for 5 seconds.



• Enter the code "1, 2, 3, 4, 5, 6, 7, 0, 0, 0"



• Press "PROGRAMMING."



• Press and hold "CONTINUE" for 5 seconds.



• Press "CONTINUE."



• Select the file to flash. [2024DarkHorseR_V5] The picture is for illustrative purposes.



• When prompted, turn the ignition switch off, the flash is complete.

